



WHEN PROTECTION MEANS EVERYTHING.

# HEIMAN FIRE EQUIPMENT THUNDERSTORM SLIDE IN UNIT

The  
**HEIMAN THUNDERSTORM SLIDE IN UNIT**  
is built for the rigors of the fire service with the  
highest quality components to maximize the  
integrity, durability, and life of the unit.



standard base price

**\$12,695<sup>00</sup>**

shipping & delivery charge not included

pictured with additional  
features and options

heimanfire.com



\*pictured with some additional options and upgrades  
\*foam cell optional

## STANDARD FEATURES

- 24 HP Honda engine
- Booster reel, 1" with manual rewind
- 100' 1" booster hose
- 3 piece Elkhart valves with NH thread and ball control handles
- Tank to pump line with valve
  - High Pressure: 2" valve
  - High Volume: 2.5" valve
- 3 gal fuel tank with G3 Fire copoly mounting bracket
- Push/Pull control rod for tank to pump
- Stainless steel manifold
- Expandable discharge manifold with garden hose discharge/drain
  - High pressure model: (1) 1.5" gate valve
  - High volume model: 2.5" x (2) 1.5" gated wye
- Liquid filled gauge on discharge manifold
- 2 1/2" inlet with cap
- 1" tank fill line
- Heavy duty Guzzler hand primer with metal top
- One year warranty on the unit


## DIMENSIONS

94" L x 48" W

|                   |                   |
|-------------------|-------------------|
| 250 gallon: 52" H | 400 gallon: 66" H |
| 300 gallon: 56" H | 500 gallon: 74" H |



Completely enclosed control panel with on/off start, low pressure protection override, vernier throttle, choke, liquid filled gauge, low oil light, & light shield with LED light



**"HOT SWAP"**  
Field replaceable pump end technology



Weather proof electrical box & high pressure flexline plumbing with stainless steel couplings



Elkhart valves with ball control handles on a painted stainless steel manifold



Powder-coated pump base



Push button electric rewind system



3 gal fuel tank with copoly mounting bracket



- Removable top with sleek stainless steel bolts
- Clearly labeled & color coded foam and water fill towers with strainer

Choice of **PUMPS**

**STANDARD HIGH-PRESSURE PUMP**

- 4-Stage Hotshot Pump Standard
- Honda engine
- Rotary & mechanical seals
- Centrifugal pump
- Sealed ball bearings
- Brass wear ring
- Stainless steel shaft
- Belt driven speed increaser for lower rpm's and higher pressure

**HIGH VOLUME PUMP**

- Aluminum alloy pump casing
- Bronze impeller
- Stainless steel shaft
- Mechanical shaft seal

**REPLACE YOUR ENTIRE PUMP IN MINUTES!**

The Thunderstorm Slide in Unit now comes plumbed ready for our exclusive "hot swap" quick change pump technology allowing users to quickly and easily field replace the Hot Shot 4 pump with minimal tools, because sometimes things happen. Purchase our optional pump end replacement kit and never be without a pump in the field.



Quick-release clamp & pump end

**KIT INCLUDES**

- Hot Shot 4 or Hellcat X2 pump end with quick-release clamp & 2 grooved bolt-on coupling clamps
- (1) 8" adjustable wrench
- (1) 7/16" wrench
- (1) 11/16" wrench

Release the clamp, use the wrenches to remove the bolt-on couplings, and then replace pump end with new one.

**HIGH PRESSURE/MID RANGE "HOT SWAP" FIELD REPLACEABLE PUMPS**

| <b>4-STAGE</b> 4087-100032<br>MAX PRESSURE: 440 PSI   MAX FLOW: 106 GPM | <b>MID RANGE</b> 4087-100067<br>MAX PRESSURE: 200 PSI   MAX FLOW: 300 GPM |
|---|---|
| 430 psi @ 10 gpm  | 290 gpm @ 10 psi  |
| 415 psi @ 20 gpm  | 275 gpm @ 50 psi  |
| 350 psi @ 65 gpm  | 215 gpm @ 100 psi   |
| 250 psi @ 94 gpm  | 112 gpm @ 150 psi   |
| 150 psi @ 105 gpm   | 50 gpm @ 175 psi  |

**ADDITIONAL OPTIONAL PUMPS & PERFORMANCE**

| <b>2-STAGE</b><br>3266-HHP24-H | <b>HALE</b><br>3266-HAL30024H | <b>DARLEY</b><br>3266-DAR24H |
|--------------------------------|-------------------------------|------------------------------|
| 325 psi @ 35 gpm               | 380 gpm @ 25 psi              | 390 gpm @ 25 psi             |
| 295 psi @ 50 gpm               | 320 gpm @ 50 psi              | 300 gpm @ 70 psi             |
| 200 psi @ 90 gpm               | 240 gpm @ 75 psi              | 180 gpm @ 120 psi            |
| 150 psi @ 120 gpm              | 150 gpm @ 100 psi             | 95 gpm @ 150 psi             |

Standard **TANK** features

Engineered to withstand the rigors of the fire service, G3 Fire® MAGNITUDE copolymer polypropylene is UV stabilized with 10x the impact strength of standard polypropylene even through wide temperature ranges.

- 250 gallon, lightweight & corrosion resistant G3 Fire® MAGNITUDE copolymer polypropylene tank with limited lifetime warranty
- Full NFPA baffling
- Removable top for cleaning & service
- Built-in water sight gauge
- An internal sump designed for maximum water usage

**ADDITIONAL INSTALLED OPTIONS & ACCESSORIES**



Push button electric rewind system  
**+ \$585<sup>00</sup>**



Scotty foam system  
**+ \$1100<sup>00</sup>**



copolymer polypropylene hose tray  
**+ \$445<sup>00</sup>**



water level indicator  
**+ \$655<sup>00</sup>**



2.5" inlet w/cap and optional valve  
**+ \$525<sup>00</sup>**



Silvex Plus or Phos Chek foam  
**+ \$135<sup>00</sup>/pail**



Bubble Cup nozzle  
1" 10/24 gpm  
**+ \$370<sup>00</sup>**



Tip 1.5" 20/60 gpm  
**+ \$99<sup>00</sup>**



LED work light  
**+ \$175<sup>00</sup>**

**HIGH PRESSURE/MEDIUM VOLUME PUMP**

- 4087-100108..... HONDA HIGH PRESSURE 4 STAGE..... [STANDARD] \$ \_\_\_\_\_
- 3266-HHP24-H..... HONDA HIGH PRESSURE ..... [ADD \$470] \$ \_\_\_\_\_

**HIGH VOLUME/MEDIUM PRESSURE PUMP**

- 4087-100122 ..... HONDA MID-RANGE 2-STAGE ..... [NO CHARGE] \$ \_\_\_\_\_
- 3266-HAL30024H ..... HONDA HIGH VOLUME (HALE)..... [ADD \$260] \$ \_\_\_\_\_
- 3266-DAR24H..... HONDA HIGH VOLUME (DARLEY) ..... [ADD \$370] \$ \_\_\_\_\_
- OTHER: PLEASE SPECIFY \_\_\_\_\_ [ADD \_\_\_\_\_] \$ \_\_\_\_\_

- 4000-T-H200..... 200 GALLON COPOLY TANK \_\_\_\_\_ foam cell..... [DEDUCT \$100] \$ \_\_\_\_\_
- 4000-T-H250..... 250 GALLON COPOLY TANK \_\_\_\_\_ foam cell..... [STANDARD] \$ \_\_\_\_\_
- 4000-T-H300..... 300 GALLON COPOLY TANK \_\_\_\_\_ foam cell..... [ADD \$450] \$ \_\_\_\_\_
- 4000-T-H400..... 400 GALLON COPOLY TANK \_\_\_\_\_ foam cell..... [ADD \$1000] \$ \_\_\_\_\_
- 4000-T-H500..... 500 GALLON COPOLY TANK \_\_\_\_\_ foam cell..... [ADD \$1900] \$ \_\_\_\_\_
- 4000-CUSTOM TANK..... [ADD \$ \_\_\_\_\_] \$ \_\_\_\_\_
- 4000-CUSTOM SKID..... [ADD \$ \_\_\_\_\_] \$ \_\_\_\_\_

- 2904-EF32-23-24..... In place of standard manual reel ..... [ADD \$585] \$ \_\_\_\_\_
- 2904-EF4038 ..... In place of standard manual reel ..... [ADD \$275] \$ \_\_\_\_\_
- 2904-FH3..... ROLLER & SPOOL ASSEMBLY ON REEL: [ ]top [ ]bottom.. [ADD \$275 ea] \$ \_\_\_\_\_
- 2930-575..... ADDITIONAL 50' OF 1" BOOSTER HOSE..... [ADD \$290] \$ \_\_\_\_\_
- SECOND REEL..... Electric Rewind, on top of tank, includes plumbing (add hose) ..... [ADD \$1700] \$ \_\_\_\_\_
- 1111-32..... NO HOSE REEL..... [DEDUCT \$390] \$ \_\_\_\_\_
- 1111-33..... NO STANDARD 100' BOOSTER HOSE ..... [DEDUCT \$400] \$ \_\_\_\_\_
- 2118-BLCHY ..... Lightweight, easy handling lead-in booster hose, 12.5' ..... [ADD \$83] \$ \_\_\_\_\_

- 1242-S106-1600 ..... FOAM PRO SYSTEM, INSTALLED *with integrated 10 gal foam cell*..... [ADD \$6,700] \$ \_\_\_\_\_
- 3306-4072-H/cell..... SCOTTY FOAM SYSTEM, INSTALLED *with integrated 10 gal foam cell*... [ADD \$1,100] \$ \_\_\_\_\_
- 3306-4074-H/pickup..... SCOTTY FOAM SYSTEM, INSTALLED  
*with pick up tube and threaded cap for department supplied foam pails* ..... [ADD \$550] \$ \_\_\_\_\_

- 1430-08825001-FPMN ... GATED INLET, ELKHART ..... [ADD \$525] \$ \_\_\_\_\_
- 1430-08815101-MPMN .. Additional 1.5" DISCHARGE W/ VALVE ..... [ADD \$395] \$ \_\_\_\_\_
- 4000-CPPHT ..... COPOLY HOSE THROUGH for 1.5" hose [ ] PS [ ] DS..... [ADD \$445] \$ \_\_\_\_\_
- 2803-ITL-4L..... HALE/CLASS 1 WATER LEVEL LIGHT GAUGE ..... [ADD \$655] \$ \_\_\_\_\_
- 1111-INSTALL ..... INSTALL MASTER SWITCH, UNIT, AND WIRE..... [ADD \$475] \$ \_\_\_\_\_
- 4109-H71030401 ..... LED WORK LIGHT ..... [ADD \$175] \$ \_\_\_\_\_
- 4087-250238..... 12 VOLT ELECTRIC PISTON PRIMER INSTALLED ..... [ADD \$795] \$ \_\_\_\_\_
- 4087-600006..... PUMP END REPLACEMENT KIT (4-STAGE) HOT SHOT 4 ..... [ADD \$1925] \$ \_\_\_\_\_
- 4087-600007..... PUMP END REPLACEMENT KIT (MIDRANGE) HELLCAT X2..... [ADD \$1925] \$ \_\_\_\_\_
- UNDER SKID STORAGE COMPARTMENT W/DOOR ..... [ADD \$1300] \$ \_\_\_\_\_
- CROSSLAY PLUMBED..... [ADD \$1200] \$ \_\_\_\_\_
- \_\_\_\_\_ [ADD \$ \_\_\_\_\_] \$ \_\_\_\_\_
- \_\_\_\_\_ [ADD \$ \_\_\_\_\_] \$ \_\_\_\_\_
- \_\_\_\_\_ [ADD \$ \_\_\_\_\_] \$ \_\_\_\_\_
- \_\_\_\_\_ [ADD \$ \_\_\_\_\_] \$ \_\_\_\_\_
- \_\_\_\_\_ [ADD \$ \_\_\_\_\_] \$ \_\_\_\_\_
- \_\_\_\_\_ [ADD \$ \_\_\_\_\_] \$ \_\_\_\_\_

**TOTAL** \$ \_\_\_\_\_

Remarks: \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

Date: \_\_\_\_\_ Salesperson: \_\_\_\_\_

Fire Dept: \_\_\_\_\_

Contact: \_\_\_\_\_

Phone #: \_\_\_\_\_

Email: \_\_\_\_\_

CUSTOMER REQUIRED TO HAVE FORKLIFT AVAILABLE FOR UNLOADING. \*FOR UNITS OVER 7', EXTENDED FORKLIFT REQUIRED

Call your salesman for more options & pricing